

■アルミ合金 配管用継手・管 在庫表

[A5052TD-O]

型
材

配
管
用

径の呼び		厚さ 外径	S10S	S20S	S40	S80	90°		45°				
A	B	D	厚さ t	厚さ t	厚さ t	厚さ t	規格値 F	計測値 F'	規格値 H	S10S	S20S	S40	S80
										計測値H'			
15	1/2	21.7			2.8	3.7	38.1	49.0	15.8			21.3	21.9
20	3/4	27.2	2.1	2.5	2.9	3.9	38.1	51.7	15.8	18.8	19.1	19.4	20.1
25	1	34.0	2.8	3.0	3.4	4.5	38.1	55.1	15.8	16.9	17.0	17.3	18.1
32	1 1/4	42.7	2.8	3.0	3.6	4.9	47.6	69.0	19.7	20.5	20.7	21.1	22.0
40	1 1/2	48.6	2.8	3.0	3.7	5.1	57.2	81.5	23.7	25.2	25.4	25.9	26.9
50	2	60.5	2.8	3.5	3.9	5.5	76.2	106.5	31.6	34.5	35.0	35.3	36.4
65	2 1/2	76.3	3.0	3.5	5.2	7.0	95.3	133.5	39.5	42.5	42.9	44.1	45.4
80	3	89.1	3.0	4.0	5.5	7.6	114.3	158.9	47.3	51.4	52.2	53.2	54.7
90	3 1/2	101.6	3.0	4.0			133.4	184.2	55.3	60.5	61.2		
100	4	114.3	3.0	4.0	6.0	8.6	152.4	209.6	63.1	69.5	70.2	71.6	73.4
125	5	139.8	3.4	5.0	6.6	9.5	190.5	260.4	78.9	87.7	88.8	90.0	92.0
150	6	165.2	3.4	5.0	7.1		228.6	311.2	94.7	105.7	106.8	108.3	

径の呼び		厚さ 外径	S10S	S20S	S40	S80	90°		45°				
A	B	D	厚さ t	厚さ t	厚さ t	厚さ t	規格値 F	計測値 F'	規格値 H	S10S	S20S	S40	S80
										計測値H'			
25	1	34.0	2.8	3.0	3.4		25.4	42.4	10.5	7.9	8.1	8.3	
32	1 1/4	42.7	2.8	3.0	3.6		31.8	53.2	13.2	9.4	9.5	9.9	
40	1 1/2	48.6	2.8	3.0	3.7	5.1	38.1	62.4	15.8	11.7	11.9	12.4	13.4
50	2	60.5	2.8	3.5	3.9	5.5	50.8	81.1	21.0	16.5	17.0	17.3	18.4
65	2 1/2	76.3	3.0	3.5	5.2	7.0	63.5	101.7	26.3	20.0	20.4	21.6	22.9
80	3	89.1	3.0	4.0	5.5	7.6	76.2	120.8	31.6	24.5	25.2	26.3	27.8
90	3 1/2	101.6	3.0				88.9	139.7	36.8	29.1			
100	4	114.3	3.0	4.0	6.0	8.6	101.6	158.8	42.1	33.6	34.3	35.7	37.5
125	5	139.8	3.4	5.0	6.6	9.5	127.0	196.9	52.6	42.8	43.9	45.0	47.1
150	6	165.2	3.4	5.0	7.1		152.4	235.0	63.1	51.8	52.9	54.4	
200	8	216.3	4.0				203.2	311.4	84.2	70.0			